



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO		S80NS			
MATERIAL		HOUSING-ABS+GF			
		LENS-PC			
		-			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHES. PER MIN		50 ~ 60			
USE VOLT.	LED	CURRNET	DC12V ~ DC24V	0.5W	MAX. 0.650A
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		φ10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1								
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4								
	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

Qlight