



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			SCDF			
MATERIAL			HOUSING-PC+GF			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	15W	MAX. 3.755A	
			DC24V		MAX. 1.788A	
			AC110V		MAX. 0.422A	
			AC220V		MAX. 0.211A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2"PF			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
	6~30	±0.1	±0.2	±0.5	±1	TITLE SCDF OUTLINE DRAWING			MODEL SCDF			
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4				DWG. NO. SCDF_OUT				
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'							±3°	
	10~50	±0°30'		±1°							±2°	
	50~120	±0°20'		±0°30'							±1°	
	120~400	±0°10'		±0°13'							±0°30'	
									SCALE N/S	SIZE A4	REV 00	SHEET 1/1

A4(297X210)