



※ \*(456) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			SMDL			
MATERIAL			HOUSING-AL			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	0.08W	MAX. 2.400A	
			DC24V		MAX. 1.255A	
			AC110V		MAX. 0.304A	
			AC220V		MAX. 0.152A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			LED STEADY/ FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-		
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2020.12.18			
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1									
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.  SMDL_OUT		SCALE	SIZE	REV	SHEET
	10~50	±0°30'		±1°	±2°						N/S	A4	00	1/1
	50~120	±0°20'		±0°30'	±1°									
	120~400	±0°10'		±0°13'	±0°30'									

A4(297X210)