



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO			SESAS			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED CLASS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	XENON	CURRENT	DC24V	6W	MAX. 1.411A	
			AC120V		MAX. 0.360A	
			AC230V		MAX. 0.220A	
VOLUME			MAX. 118dB			
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO.7.5BG 7/2			
ACTION			XENON LAMP STROBE LIGHT			

※ Voltage AC120V: AC110V-120V, AC230V: AC220V-230V

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-
	3~6	±0.05	±0.1	±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
	400~1000	±0.3	±0.8	±2	±4
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°	
	10~50	±0°30'	±1°	±2°	
	50~120	±0°20'	±0°30'	±1°	
	120~400	±0°10'	±0°13'	±0°30'	

SURFACE FINISH		-		-		1		-	
Nr.		DWG. NO.		TITLE/ NAME		MAT'L		QTY	
DSND BY		CHKD BY		CHKD BY		APRV BY		VIEW	
S.H.KIM		J.H.PARK		J.K.HAN		J.K.HAN		3	
DATE		2016.08.30		MODEL		SESAS		REFERENCE	
TITLE		SESAS OUTLINE DRAWING		DWG. NO.		SESAS_OUT		SCALE	
Qlight		N/S		SIZE		A4		REV	
						00		SHEET	
								1/1	