MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				





MODEL NO			S100MLR		
MATERIAL			HOUSING-ABS		
			LENS-AS		
			REFLECTOR-HEAT RESISTING ABS		
COLOR OF LENS			RED( ), AMBER( ), GREEN( ), BLUE( )		
FLASHES PER MIN.			120 ~ 140		
USE VOLT.	POWER LED	CURRENT	DC12V	1W	MAX. 0.183A
			DC24V		MAX. 0.127A
VOLUME			MAX. 90dB at 1m		
PROTECTION GRADE			WATER & DUST PROOF IP54		
CABLE ENTRY			ϕ9 LEAD HOLE		
COLOR OF HOUSING			MAKER STANDARD		
ACTION			POWER LED REVOLVING WARNING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH
		f	m	c	v	
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
	400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
-	-	-	-	1	-

DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30

TITLE	MODEL
S100MLR OUTLINE DRAWING	S100MLR
Qlight	DWG. NO. S100MLR_OUT

SCALE	SIZE	REV	SHEET
N/S	A4	00	1/1

A4(297X210)