



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO			SEALR-TI			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED CLASS			
			REFLECTOR-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	LED	CURRENT	DC24V	1W	0.150A	
			AC110V		0.110A	
			AC220V		0.070A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5		K.H.PARK	J.K.HAN		J.I.BAE	3	2023. 5. 3.
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		SEALR-TI			SEALR-TI		
	120~400	±0.2	±0.5	±1.2	±2.5		OUTLINE DRAWING			SEALR-TI_OUT		
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4		Qlight			DWG. NO.		
	0~10	±1°	±1°30'	±1°30'	±3°					SCALE		
	10~50	±0°30'	±1°	±1°	±2°					SIZE		
	50~120	±0°20'	±0°30'	±0°30'	±1°					REV		
	120~400	±0°10'	±0°13'	±0°30'	±0°30'					SHEET		
										1/1		