



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			STC45ML			
MATERIAL			HOUSING-ABS			
			LENS-PC			
			-			
COLOR OF LENS			CLEAR			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	0.08W	MAX. 0.110A	
			DC24V		MAX. 0.105A	
			AC110V		MAX. 0.065A	
			AC220V		MAX. 0.045A	
VOLUME			MAX. 90dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP44(Buzzer Type IP23)			
CABLE ENTRY			ø8 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			MULTIPLE COLORS LED SIGNAL STEADY/ FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	⊙	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6	±0.05	±0.1	±0.3	±0.5			S.H.KIM	J.H.PARK	J.K.HAN	J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1			TITLE					
	30~120	±0.15	±0.3	±0.8	±1.5			STC45ML OUTLINE DRAWING					
	120~400	±0.2	±0.5	±1.2	±2.5			MODEL					
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±1°	±3°			STC45ML					
	10~50	±0°30'	±1°	±1°	±2°			STC45ML_OUT					
	50~120	±0°20'	±0°30'	±0°30'	±1°			DWG. NO.					
	120~400	±0°10'	±0°13'	±0°13'	±0°30'			SCALE					
								N/S					
								SIZE	REV	SHEET			
								A4	00	1/1			

Qlight