


MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SKLR			
MATERIAL			HOUSING-PC			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
REV. PER MIN.			120 ~ 140			
USE VOLT.	POWER LED	CURRENT	DC12V	1W	MAX. 0.422A	
			DC24V		MAX. 0.266A	
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			POWER LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v	
	0.5~3			±0.2	-	
	3~6	±0.05	±0.1	±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4	
	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
TITLE			MODEL			
SKLR OUTLINE DRAWING			SKLR			
			DWG. NO.			
			SKLR_OUT			
SCALE	SIZE	REV	SHEET			
N/S	A4	00	1/1			