



LAYER	L
1	205
2	250
3	295
4	340
5	385

M20x2.5 THREAD

MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			STA35SLM			
MATERIAL			HOUSING-AL			
			LENS-AS			
			-			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    ), WHITE(    )			
USE VOLT.	LED	CURRENT	DC12V	0.08W	0.100A	LAYER1
			DC24V		0.050A	LAYER1
			AC110V		0.020A	LAYER1
			AC220V		0.020A	LAYER1
PROTECTION GRADE			WATER & DUST PROOF IP44			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-		
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v			Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20				
	3~6			±0.3	±0.5										
	6~30	±0.1	±0.2	±0.5	±1										
	30~120	±0.15	±0.3	±0.8	±1.5										
	120~400	±0.2	±0.5	±1.2	±2.5										
400~1000	±0.3	±0.8	±2	±4											
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. STA35SLM_OUT		SCALE N/S		SIZE A4	REV 00	SHEET 1/1
	10~50	±0°30'		±1°	±2°										
	50~120	±0°20'		±0°30'	±1°										
	120~400	±0°10'		±0°13'	±0°30'										
									TITLE STA35SLM OUTLINE DRAWING			MODEL STA35SLM			

Qlight