



FITTING HOLES
(SCALE 6:1)

※POWER CABLE : DC TYPE - UL2464 AWG22(0.3sq X 2C) 450mm
AC TYPE - VCTFK (0.75sq) x 2C 450mm

MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO		QEL			
MATERIAL		SIDE COVER : ABS			
		LENS-PC			
		BRACKET-SUS201			
COLOR OF LENS		UNCLEAR			
MODEL		QEL-200	QEL-300	QEL-400	QEL-500
POWER CONSUMPTION	DC24V	3.5W	5W	7W	9W
	AC110V	3W	3.5W	4.5W	5W
	AC220V	3.5W	5W	6.5W	8.5W
LED		CHIP LED			
PROTECTION GRADE		NON WATER-PROOF			

MODEL	A	B	C
QEL-200	220	200	16~170
QEL-300	320	300	16~270
QEL-400	420	400	16~370
QEL-500	520	500	16~470

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	±0.3		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	3~6	±0.05	±0.1	±0.2	±0.3		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	6~30	±0.1	±0.2	±0.5	±1		C.S.GWAK	J.H.PARK		J.K.HAN	3	2021.07.27
	30~120	±0.15	±0.3	±0.8	±1.5		TITLE			MODEL		
	120~400	±0.2	±0.5	±1.2	±2.5		QEL			QEL		
	400~1000	±0.3	±0.8	±2	±4		OUTLINE DRAWING			QEL		
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°		SURFACE FINISH	Qlight			DWG. NO.		
	10~50	±0°30'	±1°	±2°						QEL		
	50~120	±0°20'	±0°30'	±1°						SCALE	SIZE	REV
	120~400	±0°10'	±0°13'	±0°30'						1/1	A4	00
												SHEET
												1/1