



MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL NO		QL9840-10			
MATERIAL		BODY-AL			
		LENS-PC			
		BRACKET-SUS			
COLOR OF LENS		TRANSLUCENT			
USE VOLT.	LED	CURRENT	DC12V~24V	CHIP LED	MAX.1.2A
PROTECTION GRADE		WATER & DUST PROOF IP67			
CABLE ENTRY		φ7			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	J.H.PARK	J.H.PARK		J.K.HAN	3	2019.07.30	
	6~30	±0.1	±0.2	±0.5	±1	TITLE			MODEL			
	30~120	±0.15	±0.3	±0.8	±1.5	QL9840-10			QL9840-10			
	120~400	±0.2	±0.5	±1.2	±2.5	OUTLINE DRAWING						
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4				DWG. NO.			
	0~10	±1°		±1°30'	±3°				QL9840-10_OUT			
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°				SCALE			
	120~400	±0°10'		±0°13'	±0°30'				N/S			
								SIZE	REV	SHEET		
								A4	00	1/1		