



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			SCDFS			
MATERIAL			HOUSING-PC+GF			
			LENS-PC			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	6W	2.933A	
			DC24V		1.411A	
			AC110V		0.360A	
			AC220V		0.220A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2"PF			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-		
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE		
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30		
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1									
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.  SCDFS_OUT					
	10~50	±0°30'		±1°	±2°									
	50~120	±0°20'		±0°30'	±1°									
	120~400	±0°10'		±0°13'	±0°30'									
						TITLE SCDFS OUTLINE DRAWING			MODEL SCDFS					
									SCALE N/S			SIZE A4	REV 00	SHEET 1/1

**Qlight**

A4(297X210)