



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			STND125L			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			-			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHES. PER MIN			60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V ~ DC24V	0.5W	MAX. 0.565A	
			AC110V AC220V		MAX. 0.210A	
VOLUME			MAX. 105dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	<div>TITLE</div> <div>STND125L OUTLINE DRAWING</div> <div></div>			MODEL STND125L			
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°				DWG. NO. STND125L_OUT			
	120~400	±0°10'		±0°13'	±0°30'							
									SCALE N/S	SIZE A4	REV 00	SHEET 1/1



SCALE	SIZE	REV	SHEET
N/S	A4	00	1/1

A4(297X210)