



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO	S80SOL
MATERIAL	HOUSING-ABS
	LENS-PC
	REFLECTOR-HEAT RESISTING ABS
COLOR OF LENS	RED(), AMBER()
FLASHES PER MIN.	60 ~ 80
BATTERY CAPA.	2.4V
FLASHES PER MIN.	0.7Ah
CONTINUOUS OPERATING TIME WITH NO CHARGE	30Hr
PROTECTION GRADE	WATER & DUST PROOF IP54
COLOR OF HOUSING	MAKER STANDARD
ACTION	SOLAR CELL LED FLASHING LIGHT

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY Y.C.KO	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2017.11.01
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1		TITLE S80SOL OUTLINE DRAWING		MODEL S80SOL			
	30~120	±0.15	±0.3	±0.8	±1.5					DWG. NO. S80SOL_OUT		
	120~400	±0.2	±0.5	±1.2	±2.5						SCALE N/S	SIZE A4
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							