



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO	S125SOL
MATERIAL	HOUSING-ABS
	LENS-PC
	REFLECTOR-HEAT RESISTING ABS
COLOR OF LENS	RED(), AMBER()
FLASHES PER MIN.	60 ~ 80
BATTERY CAPA.	2.4V
FLASHES PER MIN.	0.7Ah
CONTINUOUS OPERATING TIME WITH NO CHARGE	50Hr
PROTECTION GRADE	WATER & DUST PROOF IP54
COLOR OF HOUSING	MAKER STANDARD
ACTION	SOLAR CELL LED FLASHING LIGHT

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH
FOR LINEAR DIMENSIONS		f	m	(C)	v	
	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4	
	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
DSND BY Y.C.KO	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2017.11.01
TITLE S125SOL OUTLINE DRAWING			MODEL S125SOL		
			DWG. NO. S125SOL_OUT		
			SCALE N/S	SIZE A4	REV 00
				SHEET 1/1	

A4(297X210)