



Ø23 CABLE ENTRY



PCD 54~56



4-Ø6 HOLES(SLOT)



FITTING HOLES(SCALE 3:1)

MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			Q125LW		
MATERIAL			HOUSING-ABS		
			LENS-PC		
			BRACKET-PC		
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()		
FLASHES PER MIN.			60 ~ 80		
USE VOLT.	LED	CURRENT	DC12V ~ 24V	0.08W	MAX. 0.255A
			AC110V ~ 220V		MAX. 0.067A
VOLUME			MAX. 80dB at 1m		
PROTECTION GRADE			WATER & DUST PROOF IP65		
CABLE ENTRY			ø23 LEAD HOLE		
COLOR OF HOUSING			MAKER STANDARD		
ACTION			LED STEADY/FLASHING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-	
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30		
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1	TITLE Q125LW OUTLINE DRAWING		MODEL Q125LW					
	30~120	±0.15	±0.3	±0.8	±1.5				DWG. NO. Q125LW_OUT	SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	120~400	±0.2	±0.5	±1.2	±2.5								
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

A4(297X210)