



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		QWH50T	
MATERIAL		HORN-PC+ABS	
		HOUSING-PC+ABS	
		-	
USE VOLT.	CURRENT	DC12V ~ 24V	MAX. 3.480A
		AC110V ~ 220V	MAX. 0.460A
CHANNEL		BIT INPUT	5CH (ONLY SD-CARD)
		BINARY INPUT	31CH
KIND OF SOUND	VOLUME	WARNING SOUNDS 31ch	MAX. 123dB at 1m
		MP3 SOUNDS	MAX. 118dB at 1m
PROTECTION GRADE		WATER & DUST PROOF - IP66	
CABLE ENTRY		CABLE GLAND "PG13.5" x 2	
COLOR OF HOUSING		MAKER STANDARD	

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-						
FOR LINEAR DIMENSIONS		f	m	(C)	v		Nr.	DWG. NO.	TITLE/ NAME			MAT'L	QT'Y
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY			APRV BY	VIEW	DATE
	3~6			±0.3	±0.5	C.S.GWAK	J.H.PARK				J.K.HAN	3	2021.10.08
	6~30	±0.1	±0.2	±0.5	±1	TITLE			QWH50T				
	30~120	±0.15	±0.3	±0.8	±1.5	QWH50T			MODEL				
	120~400	±0.2	±0.5	±1.2	±2.5	OUTLINE DRAWING			QWH50T				
	400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.				
	10~50	±0°30'		±1°	±2°				QWH50T_OUT				
	50~120	±0°20'		±0°30'	±1°				SCALE	SIZE	REV	SHEET	
	120~400	±0°10'		±0°13'	±0°30'				1/1	A4	01	1/1	