



※ *(456) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			SMDLR			
MATERIAL			HOUSING-AL			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	LED	CURRENT	DC12V	1W	MAX. 2.522A	
			DC24V		MAX. 1.322A	
			AC110V		MAX. 0.326A	
			AC220V		MAX. 0.163A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-			
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE			
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2020.12.28				
	3~6			±0.3	±0.5										
	6~30	±0.1	±0.2	±0.5	±1	TITLE SMDLR OUTLINE DRAWING			MODEL SMDLR						
	30~120	±0.15	±0.3	±0.8	±1.5										
	120~400	±0.2	±0.5	±1.2	±2.5										
400~1000	±0.3	±0.8	±2	±4				DWG. NO. SMDLR_OUT							
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°								SCALE N/S		SIZE A4	
	10~50	±0°30'	±1°	±2°											
	50~120	±0°20'	±0°30'	±1°											
	120~400	±0°10'	±0°13'	±0°30'											

A4(297X210)