



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			S100U		
MATERIAL			HOUSING-ABS		
			LENS-AS		
			REFLECTOR-HEAT RESISTING ABS		
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()		
REV. PER MIN.			120 ~ 140		
USE VOLT.	BULB	CURRENT	DC12V	10W	MAX. 0.966A
			DC24V		MAX. 0.566A
			AC110V		MAX. 0.130A
			AC220V		MAX. 0.065A
VOLUME			MAX. 90dB at 1m		
PROTECTION GRADE			WATER & DUST PROOF IP44		
CABLE ENTRY			ø10 LEAD HOLE		
COLOR OF HOUSING			MAKER STANDARD		
ACTION			BULB REVOLVING WARNING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1		TITLE S100U OUTLINE DRAWING		MODEL S100U			
	30~120	±0.15	±0.3	±0.8	±1.5					DWG. NO. S100U_OUT		
	120~400	±0.2	±0.5	±1.2	±2.5	SCALE N/S					SIZE A4	REV 00
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							