




MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			S125U			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	10W	MAX. 0.966A	
			DC24V		MAX. 0.566A	
			AC110V		MAX. 0.130A	
			AC220V		MAX. 0.065A	
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB REVOLV'ING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE / NAME		MAT'L	QT'Y
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
	6~30	±0.1	±0.2	±0.5	±1	TITLE			MODEL			
	30~120	±0.15	±0.3	±0.8	±1.5	S125U OUTLINE DRAWING			S125U			
	120~400	±0.2	±0.5	±1.2	±2.5				DWG. NO.			
400~1000	±0.3	±0.8	±2	±4	S125U_OUT							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				SCALE	SIZE	REV	SHEET
	10~50	±0°30'		±1°	±2°				N/S	A4	00	1/1
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							