



SIDE VIEW

※POWER CABLE : DURA & Flex-F VU(0.5sq.x2C) 450mm

MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	QMFL300-Ex-24		
MATERIAL	HOUSING-AL		
	LENS-TEMPERED GLASS		
	SIDE COVER-AL		
	BRACKET-SPC-1		
COLOR OF LENS	UNCLEAR		
CURRENT	VOLTAGE	MAX. 0.41A	DC24V
LED	CHIP LED		
PROTECTION GRADE	WATER & DUST PROOF IP67 / IP69K		
CABLE ENTRY	M12		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	3~6	±0.05	±0.1	±0.3	±0.5			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	6~30	±0.1	±0.2	±0.5	±1			S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	30~120	±0.15	±0.3	±0.8	±1.5			TITLE QMFL300-Ex-24 OUTLINE DRAWING					
	120~400	±0.2	±0.5	±1.2	±2.5			MODEL QMFL300-Ex-24					
	400~1000	±0.3	±0.8	±2	±4			DWG. NO. QMFL300-Ex-24_OUT					
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°				SCALE N/S					
	10~50	±0°30'	±1°	±2°				SIZE A4					
	50~120	±0°20'	±0°30'	±1°				REV 00					
	120~400	±0°10'	±0°13'	±0°30'				SHEET 1/1					

