



FITTING HOLE
(SCALE 2:1)

MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO		SM40		
MATERIAL		HOUSING-ABS		
USE VOLT.	CURRENT	DC12V	6.778A	
		DC24V	3.666A	
		AC110V	1.000A	
		AC220V	0.722A	
VOLUME		MAX. 116dB		
CABLE ENTRY		ø22 LEAD HOLE		
COLOR		RED		
RATING		10 MIN.		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. SM40_OUT			
	10~50	±0°30'		±1°	±2°				SCALE N/S			
	50~120	±0°20'		±0°30'	±1°				SIZE A4			
	120~400	±0°10'		±0°13'	±0°30'				REV 00			
									SHEET 1/1			

Qlight

A4(297X210)